IF IT WORX, IT'S UTAX

PRODUCT OVERVIEW

CONTENTS

COLOUR SYSTEMS

A3 Multifunctional Systems 3

A4 Multifunctional Systems 5

A4 Print Systems 8

B/W SYSTEMS

A3 Multifunctional Systems 9

A4 Multifunctional Systems 13

A3 Print System 17

A4 Print Systems 18

A3 MULTIFUNCTIONAL SYSTEMS

		P-C2480i MFP	2506ci	3206ci	4006ci
COPY	Copy speed	24 A4 pages/min, max 12 A3 pages/min in colour and in b/w	25 A4 / 12 A3 pages/min in colour and b/w	32 A4 / 16 A3 pages/min in colour and b/w	40 A4 / 20 A3 pages/min in colour and b/w
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256	256
	Standard paper feed	600 (500 + 100 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)
	Optional paper feed	1 or 2 x 500 sheets	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible
	Paper capacity, max	1,600 sheets	7,150 sheets	7,150 sheets	7,150 sheets
	Paper format	A6R-A3	A6R-SRA3/A3+	A6R–SRA3/A3+	A6R–SRA3/A3+
	Original feeder	Standard	Option: DP-7100, DP-7110 or DP-7120	Option: DP-7100, DP-7110 or DP-7120	Option: DP-7100 or DP-7110
	Duplex	Standard	Standard	Standard	Standard
	System memory	1.5 GB (max 3 GB)	4 GB RAM, 32 GB SSD/320 GB HDD	4 GB RAM, 32 GB SSD/320 GB HDD	4 GB RAM, 8 GB SSD/320 GB HDD
	Zoom	25%-400%	25%-400%	25%–400%	25%–400%
	Cabinet	Option: no. 62	Option: no. 76	Option: no. 76	Option: no. 76
PRINT	Type	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host (2), NFC, Wi-Fi	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8
	Emulations	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc, PDF 1.7	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc
NETWORK	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016
SCAN	Scan type	CIS colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP	TCP/IP	TCP/IP	TCP/IP
FAX	Originals	max A3	max A3	max A3	max A3
	Modem speed	33.6 kbps	33.6 kbps	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	100/200	1,000/2,000	1,000/2,000	1,000/2,000

Optional features are marked in orange font.

A3 MULTIFUNCTIONAL SYSTEMS

		5006ci	6006ci	7006ci	8006ci
COPY	Copy speed	50 A4 / 25 A3 pages/min in colour and b/w	55 A4 / 27 A3 pages/min in colour, 60 A4 / 30 A3 pages/min in b/w	65/70 A4 / 32/35 A3 pages/min in colour and b/w	70/80 A4 / 35/40 A3 pages/min in colour and b/w
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256	256
	Standard paper feed	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	4,150 (2 x 500 + 2 x 1,500 + 150 sheets)	4,150 (2 x 500 + 2 x 1,500 + 150 sheets)
	Optional paper feed	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible
	Paper capacity, max	7,150 sheets	7,150 sheets	7,650 sheets	7,650 sheets
	Paper format	A6R–SRA3/A3+	A6R–SRA3/A3+	A6R–A3+	A6R–A3+
	Original feeder	Option: DP-7100 or DP-7110	Option: DP-7100 or DP-7110	Standard	Standard
	Duplex	Standard	Standard	Standard	Standard
	System memory	4 GB RAM, 8 GB SSD/320 GB HDD	4 GB RAM, 8 GB SSD/320 GB HDD	4.5 GB RAM, 8 GB SSD/320 GB HDD	4.5 GB RAM, 8 GB SSD/320 GB HDD
	Zoom	25%–400%	25%–400%	25%–400%	25%–400%
	Cabinet	Option: no. 76	Option: no. 76	—	—
PRINT	Type	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8
	Emulations	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc
NETWORK	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016
SCAN	Scan type	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP	TCP/IP	TCP/IP	TCP/IP
FAX	Originals	max A3	max A3	max A3	max A3
	Modem speed	33.6 kbps	33.6 kbps	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	1,000/2,000	1,000/2,000	1,000/2,000	1,000/2,000

Optional features are marked in orange font

A4 MULTIFUNCTIONAL SYSTEMS

		301ci	350ci	400ci
COPY	Copy speed	30 A4 pages/min in colour and b/w	35 A4 pages/min in colour and b/w	40 A4 pages/min in colour and b/w
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256
	Standard paper feed	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)
	Optional paper feed	1 x 500 + 2 x 500 or 1 x 2,000 sheets	1 x 500 + 2 x 500 or 1 x 2,000 sheets	1 x 500 + 2 x 500 or 1 x 2,000 sheets
	Paper capacity, max	3,100 sheets	3,100 sheets	3,100 sheets
	Paper format	A6R–A4	A6R–A4	A6R–A4
	Original feeder	Standard	Option: DP-5100 or DP-5110	Option: DP-5100 or DP-5110
	Duplex	Standard	Standard	Standard
	System memory	1 GB RAM (max 2 GB RAM)	2 GB RAM, 8 GB SSD/320 GB HDD	2 GB RAM, 320 GB HDD
	Zoom	25%-400%	25%-400%	25%-400%
	Cabinet	Option: high no. 74, low no. 75	Option: high no. 74, low no. 75	Option: high no. 74, low no. 75
PRINT	Type	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0 (opt.), 10/100/1000BaseTX, USB host (2)	USB 2.0 (opt.), 10/100/1000BaseTX, USB host (3)	USB 2.0 (opt.), 10/100/1000BaseTX, USB host (3)
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5	Windows XP, Vista, 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5	Windows XP, Vista, 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5
	Emulations	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, OpenXPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, OpenXPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, OpenXPS
NETWORK	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows XP, Vista, 7/8/8.1/10, Server 2003/2008 R2/2012 R2	Windows XP, Vista, 7/8/8.1/10, Server 2003/2008 R2/2012 R2
SCAN	Scan type	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	Network protocols	TCP/IP	TCP/IP	TCP/IP
FAX	Originals	max A4	max A4	max A4
	Modem speed	33,6 kbps	33,6 kbps	33,6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	100/200	1,000/2,000	1,000/2,000

Optional features are marked in orange font

A4 MULTIFUNCTIONAL SYSTEMS

		P-C2155w MFP	P-C2655w MFP	356ci
COPY	Copy speed	21 A4 pages/min in colour and b/w	26 A4 pages/min in colour and b/w	35 A4 pages/min in colour and b/w
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256
	Standard paper feed	300 (1 x 250 + 50 sheets)	300 (1 x 250 + 50 sheets)	350 (1 x 250 + 100 sheets)
	Optional paper feed	1 x 250 sheets	1 x 250 sheets	3 x 500 sheets
	Paper capacity, max	550 sheets	550 sheets	1,850 sheets
	Paper format	A6R–A4	A6R–A4	A6R–A4
	Original feeder	Standard	Standard (Duplex-Scan)	Standard (Duplex-Scan)
	Duplex	Standard	Standard	Standard
	System memory	512 MB (max 1,536 MB)	512 MB (max 1,536 MB)	1,024 MB RAM (max 3,072 MB RAM)
	Zoom	25%–400%	25%–400%	25%–400%
	Cabinet	Option: no. 77	Option: no. 77	Option: high no. 72, low no. 73
PRINT	Type	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB-Host, SD-Slot, Wi-Fi	USB 2.0, 10/100/1000BaseTX, USB-Host, SD-Slot, Wi-Fi	USB 2.0, 10/100/1000 BaseTX, USB host (2)
	Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016, Linux, Mac ex OS 10.6	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016, Linux, Mac ex OS 10.6	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5
	Emulations	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, Open XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, Open XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS
NETWORK	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TC P/IP, Net BEUI
	Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016
SCAN	Scan type	CIS colour and b/w	CIS colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	Network protocols	TCP/IP	TCP/IP	TCP/IP
FAX	Originals	max A4	max A4	max A4
	Modem speed	33.6 kbps	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	22/100	100/100	100/200

Optional features are marked in orange font

A4 MULTIFUNCTIONAL SYSTEMS

		P-C3062i MFP	P-C3066i MFP	P-C3562i MFP	P-C3566i MFP
COPY	Copy speed	30 A4 pages/min in colour and b/w	30 A4 pages/min in colour and b/w	35 A4 pages/min in colour and b/w	35 A4 pages/min in colour and b/w
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256	256
	Standard paper feed	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)
	Optional paper feed	3 x 500 sheets	3 x 500 sheets	3 x 500 sheets	3 x 500 sheets
	Paper capacity, max	1,850 sheets	1,850 sheets	1,850 sheets	1,850 sheets
	Paper format	A6R–A4	A6R–A4	A6R–A4	A6R–A4
	Original feeder	Standard	Standard	Standard (Duplex-Scan)	Standard (Duplex-Scan)
	Duplex	Standard	Standard	Standard	Standard
	System memory	1,024 MB RAM (max 3,072 MB RAM)	1,024 MB RAM (max 3,072 MB RAM)	1,024 MB RAM (max 3,072 MB RAM)	1,024 MB RAM (max 3,072 MB RAM)
	Zoom	25%–400%	25%–400%	25%–400%	25%–400%
	Cabinet	Option: high no. 72, low no. 73	Option: high no. 72, low no. 73	Option: high no. 72, low no. 73	Option: high no. 72, low no. 73
PRINT	Type	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host (2)	USB 2.0, 10/100/1000 BaseTX, USB host (2)	USB 2.0, 10/100/1000BaseTX, USB host (2)	USB 2.0, 10/100/1000 BaseTX, USB host (2)
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5
	Emulations	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS
NETWORK	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TC P/IP, Net BEUI	TCP/IP, Net BEUI	TC P/IP, Net BEUI
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016
SCAN	Scan type	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	Network protocols	TCP/IP	TCP/IP	TCP/IP	TCP/IP
FAX	Originals	--	max A4	--	max A4
	Modem speed	--	33.6 kbps	--	33.6 kbps
	Compression method	--	JBIG, MMR, MR, MH	--	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	--	100/200	--	100/200

Optional features are marked in orange font

A4 PRINT SYSTEMS

	P-C2650DW	P-C3062DN	P-C3562DN	P-C4072DN
Print format	A6R–A4	A6R–A4	A6R–A4	A6R–A4
Print speed	26 A4 pages/min in colour and b/w	30 A4 pages/min in colour and b/w	35 A4 pages/min in colour and b/w	40 A4 pages/min in colour and b/w
Print resolution	600 x 600 dpi, 9,600 x 600 dpi level, 1,200 x 1,200 dpi (reduced speed)	600 x 600 dpi, max 1,200 x 1,200 dpi (reduced speed)	600 x 600 dpi, max 1,200 x 1,200 dpi (reduced speed)	600 x 600 dpi, max 1,200 x 1,200 dpi (reduced speed)
Standard paper feed	300 (1 x 250 + 50 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)
Optional paper feed	1 x 250 sheets	3 x 500 sheets	3 x 500 sheets	3 x 500 sheets
Duplex	Standard	Standard	Standard	Standard
Processor	Cortex-A9 / 800 MHz	ARM Cortex-A9 dual core / 1.2 GHz	ARM Cortex-A9 dual core / 1.2 GHz	ARM Cortex-A9 dual core / 1.2 GHz
Print memory	512 MB (max 512 MB)	1,024 MB (max 1,024 MB)	1,024 MB (max 3,072 MB)	1,024 MB (max 3,072 MB)
Interfaces	USB 2.0, 10/100/1000BaseTX, USB host, SD slot, Wi-Fi	USB 2.0, 10/100/1000BaseTX, USB host (2)	USB 2.0, 10/100/1000BaseTX, USB host (2)	USB 2.0, 10/100/1000BaseTX, USB host (2)
Network card optional	--	IB-50 Gigabit Ethernet, IB-36 / IB-51 WLAN card	IB-50 Gigabit Ethernet, IB-36 / IB-51 WLAN card	IB-50 Gigabit Ethernet, IB-36 / IB-51 WLAN card
Emulations	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, Open XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS

A3 MULTIFUNCTIONAL SYSTEMS

		1855	2256	P-2540i MFP
COPY	Copy speed	18 A4 / 8 A3 pages/min	22 A4 / 10 A3 pages/min	25 A4 / 12 A3 pages/min
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256
	Standard paper feed	400 (300 + 100 sheets)	400 (300 + 100 sheets)	600 (1 x 500 + 100 sheets)
	Optional paper feed	3 x 300 sheets	3 x 300 sheets	1 or 2 x 500 sheets
	Paper capacity, max	1,300 sheets	1,300 sheets	1,600 sheets
	Paper format	A6R–A3	A6R–A3	A6R–A3
	Original feeder	Option: DP-480	Option: DP-480	Standard
	Duplex	Option: DU-480	Option: DU-480	Standard
	System memory	256 MB	256 MB	1 GB (max 3 GB)
	Zoom	25%–400%	25%–400%	25%–400%
	Cabinet	Option: high no. 68, low no. 69	Option: high no. 68, low no. 69	Option: no. 62
PRINT	Type	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0	USB 2.0	USB 2.0, 10/100/1000BaseTX, USB host (2)
	Operating systems	Windows 7/8/8.1/10, Mac ex OS 10.5	Windows 7/8/8.1/10, Mac ex OS 10.5	Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5
	Emulations	GDI	GDI	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe, PDF 1.7
NETWORK	Interfaces	--	(optional)	10/100/1000BaseTX
	Network protocols	--	TCP/IP	TCP/IP, Net BEUI
	Operating systems	--	Windows 7/8/8.1/10	Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016
SCAN	Scan type	CIS colour and b/w	CIS colour and b/w	CIS colour and b/w
	Scan resolution	200, 300, 400 (only b/w), 600 (only b/w) dpi	200, 300, 400 (only b/w), 600 (only b/w) dpi	200, 300, 400, 600 dpi
	Interfaces	USB 2.0	USB 2.0	10/100/1000BaseTX, USB 2.0
	Network protocols	--	--	TCP/IP
FAX	Originals	--	max A3	max A3
	Modem speed	--	33.6 kbps	33.6 kbps
	Compression method	--	MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	--	32/120	100/200

Optional features are marked in orange font.

A3 MULTIFUNCTIONAL SYSTEMS

		3262i	4062i
COPY	Copy speed	32 A4 / 17 A3 pages/min	40 A4 / 21 A3 pages/min
	Copy resolution	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256
	Standard paper feed	1,100 (2 x 500 + 100 sheets)	1,100 (2 x 500 + 100 sheets)
	Optional paper feed	2 x 500 sheets or 2 x 1,500	2 x 500 sheets or 2 x 1,500
	Paper capacity, max	4,100 sheets	4,100 sheets
	Paper format	A6R-A3	A6R-A3
	Original feeder	Option: DP-7100, DP-7110 or DP-7120	Option: DP-7100, DP-7110 or DP-7120
	Duplex	Standard	Standard
	System memory	2 GB RAM, 32 GB SSD/320 GB HDD	2 GB RAM, 8 GB SSD/320 GB HDD
	Zoom	25%-400%	25%-400%
	Cabinet	Option: no. 70	Option: no. 70
PRINT	Type	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host, NFC	USB 2.0, 10/100/1000BaseTX, USB host, NFC
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8
	Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe
NETWORK	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016
SCAN	Scan type	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP	TCP/IP
FAX	Originals	max A3	max A3
	Modem speed	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	1,000/2,000	1,000/2,000

Optional features are marked in orange font.

A3 MULTIFUNCTIONAL SYSTEMS

		4056i	5056i	6056i
COPY	Copy speed	40 A4 / 20 A3 pages/min	50 A4 / 25 A3 pages/min	60 A4 / 30 A3 pages/min
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256
	Standard paper feed	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)
	Optional paper feed	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible
	Paper capacity, max	7,150 sheets	7,150 sheets	7,150 sheets
	Paper format	A6R–SRA3/A3+	A6R–SRA3/A3+	A6R–SRA3/A3+
	Original feeder	Option: DP-7100 or DP-7110	Option: DP-7100 or DP-7110	Option: DP-7100 or DP-7110
	Duplex	Standard	Standard	Standard
	System memory	4 GB RAM, 8 GB SSD/320 GB HDD	4 GB RAM, 8 GB SSD/320 GB HDD	4 GB RAM, 8 GB SSD/320 GB HDD
	Zoom	25%–400%	25%–400%	25%–400%
	Cabinet	Option: no. 76	Option: no. 76	Option: no. 76
PRINT	Type	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8
	Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe
NETWORK	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016
SCAN	Scan type	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP	TCP/IP	TCP/IP
FAX	Originals	max A3	max A3	max A3
	Modem speed	33.6 kbps	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	1,000/2,000	1,000/2,000	1,000/2,000

Optional features are marked in orange font.

A3 MULTIFUNCTIONAL SYSTEMS

		7056i	8056i
COPY	Copy speed	70 A4 / 35 A3 pages/min	80 A4 / 40 A3 pages/min
	Copy resolution	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256
	Standard paper feed	4,150 (2 x 500 + 2 x 1,500 + 150 sheets)	4,150 (2 x 500 + 2 x 1,500 + 150 sheets)
	Optional paper feed	2 x 500, 2 x 1.500, 3.000 sheets, different combinations possible	2 x 500, 2 x 1.500, 3.000 sheets, different combinations possible
	Paper capacity, max	7,650 sheets	7,650 sheets
	Paper format	A6R–A3+	A6R–A3+
	Original feeder	Standard	Standard
	Duplex	Standard	Standard
	System memory	4.5 GB RAM, 8 GB SSD/320 GB HDD	4.5 GB RAM, 8 GB SSD/320 GB HDD
	Zoom	25%–400%	25%–400%
	Cabinet	--	--
PRINT	Type	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8
	Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe
NETWORK	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016
SCAN	Scan type	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP	TCP/IP
FAX	Originals	max A3	max A3
	Modem speed	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	1,000/2,000	1,000/2,000

Optional features are marked in orange font.

A4 MULTIFUNCTIONAL SYSTEMS

		P-3521 MFP	P-3527w MFP
COPY	Copy speed	35 A4 pages/min	35 A4 pages/min
	Copy resolution	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256
	Standard paper feed	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)
	Optional paper feed	2 x 250 sheets	2 x 250 sheets
	Paper capacity, max	850 sheets	850 sheets
	Paper format	A6R–A4	A6R–A4
	Original feeder	Standard	Standard
	Duplex	Standard	Standard
	System memory	512 MB RAM (max 1,536 MB RAM)	512 MB RAM (max 1,536 MB RAM)
	Zoom	25%–400%	25%–400%
	Cabinet	Option: no. 78	Option: no. 78
PRINT	Type	Integrated within the system	Integrated within the system
	Interfaces	10/100/1000BaseTX, USB 2.0, USB host, SD slot	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi
	Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016, Linux, Mac ex OS 10.6	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016, Linux, Mac ex OS 10.6
	Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS
NETWORK	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2
SCAN	Scan type	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	Network protocols	TCP/IP	TCP/IP
FAX	Originals	--	max A4
	Modem speed	--	33.6 kbps
	Compression method	--	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	--	100/200

A4 MULTIFUNCTIONAL SYSTEMS

		P-4020 MFP	P-4025w MFP	P-4026iw MFP
COPY	Copy speed	40 A4 pages/min	40 A4 pages/min	40 A4 pages/min
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256
	Standard paper feed	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)
	Optional paper feed	2 x 250 sheets	2 x 250 sheets	2 x 250 sheets
	Paper capacity, max	850 sheets	850 sheets	850 sheets
	Paper format	A6R–A4	A6R–A4	A6R–A4
	Original feeder	Standard (Duplex-Scan)	Standard (Duplex-Scan)	Standard (Duplex-Scan)
	Duplex	Standard	Standard	Standard
	System memory	512 MB RAM (max 1,536 MB RAM)	512 MB RAM (max 1,536 MB RAM)	512 MB RAM (max 1,536 MB RAM)
	Zoom	25%–400%	25%–400%	25%–400%
	Cabinet	Option: no. 78	Option: no. 78	Option: no. 78
PRINT	Type	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	10/100/1000BaseTX, USB 2.0, USB host, SD slot	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi
	Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016, Linux, Mac ex OS 10.6	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016, Linux, Mac ex OS 10.6	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016, Linux, Mac ex OS 10.6
	Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS
NETWORK	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2
SCAN	Scan type	CIS colour and b/w	CIS colour and b/w	CIS colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	Network protocols	TCP/IP	TCP/IP	TCP/IP
FAX	Originals	--	max A4	max A4
	Modem speed	--	33.6 kbps	33.6 kbps
	Compression method	--	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	--	100/200	100/200

A4 MULTIFUNCTIONAL SYSTEMS

		P-4531 MFP	P-4536 MFP	P-4531i MFP	P-4536i MFP
COPY	Copy speed	45 A4 pages/min	45 A4 pages/min	45 A4 pages/min	45 A4 pages/min
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256	256
	Standard paper feed	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)
	Optional paper feed	4 x 500 sheets	4 x 500 sheets	4 x 500 sheets	4 x 500 sheets
	Paper capacity, max	2,600 sheets	2,600 sheets	2,600 sheets	2,600 sheets
	Paper format	A6R–A4	A6R–A4	A6R–A4	A6R–A4
	Original feeder	Standard	Standard	Standard	Standard
	Duplex	Standard	Standard	Standard	Standard
	System memory	1 GB RAM, (max 3 GB RAM), 32/128 GB SSD	1 GB RAM, (max 3 GB RAM), 32/128 GB SSD	1 GB RAM, (max 3 GB RAM), 32/128 GB SSD	1 GB RAM, (max 3 GB RAM), 32/128 GB SSD
	Zoom	25%–400%	25%–400%	25%–400%	25%–400%
	Cabinet	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80
PRINT	Type	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5
	Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS
NETWORK	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016
SCAN	Scan type	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	Network protocols	TCP/IP	TCP/IP	TCP/IP	TCP/IP
FAX	Originals	--	max A4	--	max A4
	Modem speed	--	33.6 kbps	--	33.6 kbps
	Compression method	--	JBIG, MMR, MR, MH	--	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	--	22/100	--	100/200

Optional features are marked in orange font.

A4 MULTIFUNCTIONAL SYSTEMS

		P-5536i MFP	P-6036i MFP
COPY	Copy speed	55 A4 pages/min	60 A4 pages/min
	Copy resolution	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256
	Standard paper feed	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)
	Optional paper feed	4 x 500 sheets	4 x 500 sheets
	Paper capacity, max	2,600 sheets	2,600 sheets
	Paper format	A6R–A4	A6R–A4
	Original feeder	Standard (Duplex-Scan)	Standard (Duplex-Scan)
	Duplex	Standard	Standard
	System memory	1 GB RAM, (max 3 GB RAM), 32/128 GB SSD	1 GB RAM, (max 3 GB RAM), 32/128 GB SSD
	Zoom	25%–400%	25%–400%
	Cabinet	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80
PRINT	Type	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5
	Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS
NETWORK	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016
SCAN	Scan type	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	Network protocols	TCP/IP	TCP/IP
FAX	Originals	max A4	max A4
	Modem speed	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	100/200	100/200

Optional features are marked in orange font.

A3 PRINT SYSTEM

	LP 3151
Print format	A6R–A3
Print speed	51 A4 / 26 A3 pages/min
Print resolution	1,200 x 1,200 dpi
Standard paper feed	1,200 (2 x 500 + 200 sheets)
Optional paper feed	2 x 500, 3,000 sheets
Duplex	Standard
Processor	PowerPC 750FL/600 MHz
Print memory	128 MB (max 640 MB)
Interfaces	IEEE 1284 parallel, USB 2.0, 10/100BaseTX, CF slot
Optional interfaces	--
Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), Line Printer, Diablo 630, Epson LQ-850, IBM Proprinter X24E, KCGL, PRESCRIBE IIe

A4 PRINT SYSTEMS

	P-3522DW	P-4020DN	P-4020DW
Print format	A6R–A4	A6R–A4	A6R–A4
Print speed	35 A4 pages/min	40 A4 pages/min	40 A4 pages/min
Print resolution	600 x 600 dpi, 1,200 x 1,200 dpi	600 x 600 dpi, 1,200 x 1,200 dpi	600 x 600 dpi, 1,200 x 1,200 dpi
Standard paper feed	350 (250 + 100 sheets)	350 (250 + 100 sheets)	350 (250 + 100 sheets)
Optional paper feed	2 x 250 sheets	2 x 250 sheets	2 x 250 sheets
Duplex	Standard	Standard	Standard
Processor	Cortex-A9 / 800 MHz	Cortex-A9 / 800 MHz	Cortex-A9 / 800 MHz
Print memory	256 MB (max 256 MB)	256 MB (max 256 MB)	256 MB (max 256 MB)
Interfaces	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi	10/100/1000BaseTX, USB 2.0, USB host, SD slot	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi
Optional interfaces	--	--	--
Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS

	P-4531DN	P-5031DN	P-5531DN	P-6031DN
Print format	A6R–A4	A6R–A4	A6R–A4	A6R–A4
Print speed	45 A4 pages/min	50 A4 pages/min	55 A4 pages/min	60 A4 pages/min
Print resolution	1,200 x 1,200 dpi	1,200 x 1,200 dpi	1,200 x 1,200 dpi	1,200 x 1,200 dpi
Standard paper feed	600 (500 + 100 sheets)	600 (500 + 100 sheets)	600 (500 + 100 sheets)	600 (500 + 100 sheets)
Optional paper feed	4 x 500 sheets	4 x 500 sheets	4 x 500 sheets	4 x 500 sheets
Duplex	Standard	Standard	Standard	Standard
Processor	Cortex-A9 / 1,200 MHz	Cortex-A9 / 1,200 MHz	Cortex-A9 / 1,200 MHz	Cortex-A9 / 1,200 MHz
Print memory	512 MB (max 2 GB)	512 MB (max 2 GB)	512 MB (max 2 GB)	512 MB (max 2 GB)
Interfaces	10/100/1000BaseTX, USB 2.0, USB host (2), SD slot	10/100/1000BaseTX, USB 2.0, USB host (2), SD slot	10/100/1000BaseTX, USB 2.0, USB host (2), SD slot	10/100/1000BaseTX, USB 2.0, USB host (2), SD slot
Optional interfaces	IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card	IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card	IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card	IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card
Emulations	PCL6 (5e, XL), KPDL 3 (PS 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PS 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PS 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PS 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, XPS, Open XPS

PRODUCT OVERVIEW 08/2018

Your UTAX dealer

UTAX has been a trade mark for professional office technology since 1961. As the partner of a German wide dealer network and international distribution, we are specialised in the distribution and integration of printing, copying and multifunctional systems in corporate IT and public sector, amongst others. With the MDS solution UTAX smart for example, output systems can be controlled regardless of the manufacturer and the infrastructure can be optimised in line with demands. UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual. UTAX and the UTAX logo are registered trade marks of TA Triumph-Adler GmbH. All other brand names referred to are registered trade marks of the respective manufacturers.

UTAX Norderstedt
www.utax.com

UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual. UTAX and the UTAX logo are registered trademarks of TA Triumph-Adler GmbH. All other brand names referred to are registered trademarks of the respective manufacturers.

08/2018